APPENDIX A

Table of Contents

A1. OVERVIEW	A-2
A2. RESPONSIBILITIES	A.2
A3. SAFETY REVIEW PROCESS	A-3
A4. PAYLOAD HAZARD ANALYSIS	A-5
A4.1 Payload Safety Matrix	A-8
A4.2 Description Data Form	A-11
A4.3 Payload Hazard Report	A-14
A4.4 Payload Safety Noncompliance Report (Waiver)	A-16
A4.5 Additional Safety Requirements	.A-18
	A-25
List of Figures	
Figure A.1 Payload Safety Review Process	A-4
Figure A.2 Hazard Analysis Process	A-7
Figure A.3 Payload Safety Matrix	A-9
Figure A.4 NSTS Payload Safety Requirements Applicability Descriptive Data Form	
Figure A.5 STS Payload Ground Safety Requirements Applicability Matrix	A-12
Figure A.6 STS Payload Safety Requirements Applicability Descriptive Data	A-13
Figure A.7 Payload Hazard Report	A-15
Figure A.8 Payload Safety Noncompliance Report	A-17
Figure A.9 Radiation Training and Experience Summary (Ionization Radiation) Form	.A-19
Figure A.10 Radioactive Material Use Request	A-20
Figure A.11 Ionizing Radiation Source Data Sheet	A-21
Figure A.11a Ionizing Radiation Source Data Sheet (Cont'd)	A-22
Figure A.12 Training and Experience Summary Non-Ionizing Radiation Users Form	.A-23
Figure A.13 Non-Ionizing Radiation Protection Source Questionnaire	A-24
Figure A.14 Payload System Safety Data Submittal Summary	A-26
Figure A.15 HH Sample Mission Experiment Safety Schedule	A-27
List of Tables	
Table A.1 Basic Hazard Groups. Causes. and Effects	A-6

APPENDIX A PAYLOAD SAFETY REQUIREMENTS

A1. OVERVIEW

All payloads using the STS must meet certain design and operational requirements prior to being considered "safe". Payloads and GSE must not be capable of generating or sustaining any failure mode that will result in a hazard to the flight and ground personnel, the STS, GSE, and other payloads. A hazard is defined as the presence of a potential risk situation caused by an unsafe act or condition that could disable or cause damage to the Orbiter, its crew, ground processing facilities or personnel during pre- and post- launch activities. Basic requirements for payload safe design and operation are provided for in the following NASA documents:

NSTS 1700.7 (current issue*) - Safety Policy Requirements for Payloads Using the Space Transportation System (STS), January 1989.

SAMTO HB S-100, KHB 1700.7 (current issue*) - Space Transportation System Payload Ground Safety Handbook.

All payloads must comply with the guidelines and requirements set in these documents.

This section summarizes information from NSTS 1700.7 latest version to aide the customer in understanding the requirements and guidelines that must be followed in order to obtain safety certification for their payload. This section is not a substitute for NSTS 1700.7 latest version which takes precedence and must be adhered to by the customer for their payload. KHB 1700.7 latest version is the governing document for the GSE and ground operations.

* Current issue includes all future changes and revisions.

A2. RESPONSIBILITIES

A customer representative should be designated as the technical point of contact between the HH Project and the customer. This representative is called the Payload Manager. The Payload Manager is responsible for assuring the safety of his payload and to implement the requirements of NSTS 1700.7 and KHB 1700.7. Each customer payload shall have a system safety support person to advise the payload manager and designers, and to act as a point of contact for safety matters. The HH Project, acting as the responsible "payload organization," interfaces with the NSTS on behalf of the group of individual payload elements or experiments and carrier systems which comprise a Shuttle payload. GSFC will assign a Mission Manager who will be the single technical point of contact for GSFC and interface with the payload Manager. The HH Project Safety Manager will support the NASA Mission Manager in the safety review process. Payload shall have a system safety support person as a member of the payload team to advise. All payload safety data will be reviewed and approved by GSFC prior to submittal to JSC/KSC.

A3. SAFETY REVIEW PROCESS

The safety review process between the customer, GSFC, and the STS begins 18-24 months prior to launch with the development of safety-related information as part of the Payload Accommodations Conference. The review process culminates just prior to launch with the Final Safety Inspection. Aspects of safety-related issues extend into flight operations as well. Figure A.1 represents an overview of the safety review process.

The system safety requirements associated with use of the Shuttle are extensive, and are intended to insure the safety of ground processing and flight personnel, as well as the Shuttle Orbiter and flight hardware. The phased safety reviews and safety data packages, through which the project demonstrates compliance with these requirements, are major mission milestones.




FIGURE A.1 PAYLOAD SAFETY REVIEW PROCESS

A4. PAYLOAD HAZARD ANALYSIS

A hazard analysis is the technique used to systematically identify, evaluate and resolve hazards. Typically, such analyses assess the entire system and its interfaces. Results of the hazard analysis leads to one or more of the following:

- Improved payload safety design,
- Development of controls to mitigate hazards,
- Establishment of acceptable risk levels.

There may be many factors contributing to a hazard, however, there are basic hazard groups that are applicable to HH payloads. Those hazard groups and representative examples of their causes and effects are summarized in Table A.1. Figure A.2 provides an overview of the hazard analysis process.

TABLE A.1 BASIC HAZARD GROUPS, CAUSES, AND EFFECTS

Hazard Type	<u>Definition</u>	Possible Cause	Possible Effect
Collision	Payloads and/or Elements Break Loose and Impact Structures, Other Payloads, or Ground Personnel	Structural Failure Procedural Error, Inadequate Ground Handling Equipment	Penetration of Payload, Personnel Injury
Contamination	Release or Accumulation of Particular Matter or The Placement of the Wrong Material in a Container	Leakage, Spillage, Outgassing, Abrasion, Improper Cleanliness Procedures, Ínappropriate Materials Usage	Degraded Atmosphere or Equipment Operation, Personnel Injury
Corrosion	Structural Degradation of Metallic and Non- Metallic Equipment	Leakage, Material Incompatibility, Environmental Extremes, Short Circuits	Mechanical Failures, Premature Wear, Seizure
Electrical shock	Electrical current passing through any portion of the body	Human error, procedural error, equipment failure, static discharge, short circuit	Personnel Injury
Explosion	Violent Release of Energy Due to Over- pressurization	Susceptible Equipment, Batteries, Pumps, Motors, Blowers, Generators, Lasers, Etc.	Payload Damage, Personnel Injury
Fire	Rapid Oxidation of Payload Element Combustibles Flammability of Materials	Fuel and Oxidizer Exposed to Ignition Source	Payload Damage, Personnel Injury
Radiation	Exposure (Human or Equipment) To: Ionizing Radiation, UV or IR Light, Lasers, Electromagnetic or RF- Generating Equipment	Leaky or Inadequate Shielding	Degraded or Damaged Payload or Equipment Personnel Injury
Temperature extremes	Exposure to abnormal temperature extremes (hot or cold)	Insulation breakdown, short circuits, seal leaks plumbing failures procedural error, human error	Degraded or damaged payload or equipment, personnel injury
Injury and Illness	Payloads Break Loose and Impact Ground Personnel and Release of Toxic Materials	Procedural Error, Inadequate Ground Handling Equipment Leakage or Spillage of Toxic Materials	Personnel Injury, Payload Penetration Degraded a Atmosphere or Equipment Operation

Hazard Analysis Process Payload Safety Matrix Applicable Safety Requirement X XX Payload Safety Requirements Waive Descriptive Data Form Matrix Comment HR# Element Subsystem Requirement Hazard Reason Acceptance Rationale Payload Hazard Subsystem Requirement Hazard Description Cause Control Verification Method Status Approval/Review Signature

FIGURE A.2 HAZARD ANALYSIS PROCESS

Safety Data Package (SDP)

A4.1 Payload Safety Matrix

The initial version of the Payload Safety Requirements Applicability Matrix is required early in the safety review cycle and should be kept up to date throughout the development process. This form and the Payload Ground Safety Requirements Applicability Matrix documents are used to foresee and assess interrelationships between the basic hazard groups and subsystems contained in the payload. Examples of these forms are presented in Figures A.3 and A.5.




FIGURE A.3 PAYLOAD SAFETY MATRIX

A-9

NSTS PAYL	OAD SAFETY REQUI	REMENTS	
APPLICA	PageOf		
DAVIOAD			Date:
PAYLOAD:	WAGARD DEDORM		Phase:
MATRIX ELEMENT REFERENCE NO.	HAZARD REPORT NUMBER	HAZARD	TITLE
REPERENCE NO.	NUMBER		
	,		
			!

JSC Form 1090A (Rev Oct 88) Previous Editions Are Obsolete

FIGURE A.4 NSTS PAYLOAD SAFETY REQUIREMENTS APPLICABILITY DESCRIPTIVE DATA FORM

A4.2 Description Data Form

Similar to the Payload Safety Matrix, the Payload Safety Requirements Applicability Descriptive Data Forms are required early in the safety cycle and must be continually updated. These forms (Figure A.4 and A.6) are completed for each subsystem having a "X" in any corresponding hazard group box on the Payload Safety Matrix. The Descriptive Data Forms provide a listing of the hazard groups applicable to each subsystem and cross-references each hazard to the applicable technical requirement from NSTS 1700.7B and KHB 1700.7, Revision A. Upon completion of the Payload Safety Matrix and the Descriptive Data Form, the customer has a comprehensive list of all the payload safety hazard issues that must be addressed in order for the payload to be granted safety certification.

NAME, ORG, INITIAL! 7. SAFETY ANALYSIS BY: ISEE INSTRUCTIONS ON REVENSE SIDE OF GSFC. 302-58-018 Z AABBCCDD PAYLOAD ORGAMIZATION PERSO > STS PAYLOAD GROUND SAFETY REQUIREMENTS × 3 > 5 ۲ S 2. PAYLOAD ORGANIZATION: Œ APPLICABILITY MATRIX K K O P Q PAYLOAD AND GSE 7 I O ш REVIEWED BY: ш ۵ ပ 8 ⋖. APPLICABLE: WAIVER REDUINED REQUIREMENTS 9 4. PAGE ENOT APPLICABLE MAZAND IDENTIFIED GIFC.201 SSORA HADI PAYLOAD AND GSE ELEMENTS 1. PAYLOAD: & LEGEND: 3. PHASE: wi

FIGURE A.5 STS PAYLOAD GROUND SAFETY REQUIREMENTS APPLICABILITY MATRIX

10. STS PAYLOAD SAFETY REQUIREMENTS APPLICABILITY DESCRIPTIVE DATA					
MATRIX ELEMENT	COMMENTS	H/R #			
ELEMENT					
	,				

GSFC-302-SS-02B (2/83)

FIGURE A.6 STS PAYLOAD SAFETY REQUIREMENTS APPLICABILITY DESCRIPTIVE DATA

A4.3 Payload Hazard Report

Following the completion of the safety analysis and identification of potential hazards, a Payload Hazard Report must be completed. This report is to be completed for each hazard identified on the Descriptive Data Form. Each hazard report should stand alone. Data required to understand the hazard, the hazard controls, and safety verification methods including the organization responsible for each verification, should be attached to the report. When functional diagrams are supplied, the pertinent information shall be clearly identified, (e.g., controls, inhibits, monitors, etc.).

Information for Hazard Reports, is to be submitted to the HH Safety Manager. This data is included in a Payload/HH combined SDP.

The hazard report is used to track hazards identified throughout the lifecycle of the payload. It contains NASA review and approval signatures, acknowledging the possibility of hazard occurring, and the result rationale that has been reviewed in accordance with NASA standards. Figure A.7 represents the Payload Hazard Report.

PAYLOAD HA	AZARD REPORT	No.
PAYLOAD		PHASE
SUBSYSTEM	HAZARD GROUP	DATE
HAZARD TITLE		
APPLICABLE SAFETY REQUIREMENT	S	HAZARD CATEGORY
		CATASTROPHIC
	<u>,</u>	CRITICAL
DESCRIPTION OF HAZARD		
HAZARD CAUSES		
HAZARD CONTROLS		
SAFETY VERIFICATION METHODS		
STATUS OF VERIFICATION		
APPROVAL	PAYLOAD ORGANIZATIO	N STS
PHASE I		
PHASE II		
PHASE III		

JSC Form 542B (Rev Nov 82)

FIGURE A.7 PAYLOAD HAZARD REPORT

A4.4 Payload Safety Noncompliance Report (Waiver)

A waiver request form (as shown in Figure A.8) must be submitted for noncompliance. This request will be returned to GSFC for review in such cases when safety requirements cannot be met. The Mission Manager will negotiate with the STS on behalf of the customer concerning the acceptability of the waiver request. Should the waiver be denied, the customer must meet the requirement through design changes to the payload or run the risk of having the payload denied the opportunity for flight on the STS.

PAYLOAD SAFET	Y NONCOMPLIAN	NCE REPORT	NO.	DATE
TITLE (Brief reference to non	compliance)			
PAYLOAD IDENTIFICATION	ON (Include reference to applic	cable payload element, subst	ystem, and/or cor	nponent)
APPLICABLE REQUIREME	NT			
DESCRIPTION OF NONCO	MPLIANCE (Specify how the	design or operation does no	t meet the safety	requirements)
HAZARD OR HAZARD CA	USE (Include reference to Pay	load Hazard Report)		
	CSE (morado reference to 1 ay	road Hazard Report)		
REASON REQUIREMENT O	CANNOT BE FULFILLED			
RATIONALE FOR ACCEPT	ANCE (Define the design feat	ure or procedure used to co	nclude that the no	oncompliance
Condition is safe. Attach app				меотришее
	Δ ΡΡΡΟΥΔΙ	L SIGNATURES	· · ·	
PAYLOAD ORGANIZATIO		2 SIGNAT CRES		DATE
WANTE	D ADDDOVAL	DEV	IATION ADD	DOVAL
EFFECTIVITY	R APPROVAL	EFFECTIVITY	IATION APP	ROVAL
STS OPERATOR	DATE	STS OPERATOR	<u></u>	DATE
JSC Form 542C (Rev Mar 83)				

FIGURE A.8 PAYLOAD SAFETY NONCOMPLIANCE REPORT

A4.5 Additional Safety Requirements

Depending on the design of the payload and its operating characteristics, beginning at Phase O/I Safety Data Package (SDP) submission timeframe, the customer may be required to submit the last version of additional forms such as:

- a. Radiation Training and Experience Summary (Figure A.9)
- b. Radioactive Materials Use Request (Figure A.10)
- c. Ionizing Radiation Source Data Sheet (Figure A.11A and A.11B)
- d. Training and Experience Summary Non-Ionizing Radiation Users (KSC Form 16-450) (Figure A.12)
- e. Non-Ionizing Radiation Protection Source Questionnaire (KSC Form 16-453) (Figure A.13)

It is important to address and identify special safety requirements and document them, beginning at Phase O/I SDP as soon as possible. These requirements may include:

- a. Special handling or testing during installation or removal of the payload
- b. Special environments during certain mission phases
- c. Special flight operations.

RADIATION TRAINING AND EXPERIENCE SUMMARY (IONIZING RADIATION) Note: (Complete unshaded sections of Form only) (Please type/print legibly, prepare original and one copy)(Instructions for completion on reverse) I. GENERAL INFORMATION NAME/TELEPHONE NUMBER DATE OF BIRTH ORGANIZATION/MAILCODE OR ADDRESS AUTHORIZATION NUMBER SOCIAL SECURITY NO. TYPE OF USER SYSTEM/DEVICE TO BE USED AREA RADIATION OFFICER MAINTENANCE USER OTHER USE SPVR/CUSTODIAN II. TRAINING (Use supplemental sheets as needed) FORMAL DURATION TYPE OF TRAINING WHERE TRAINED ON-THE-JOB COURSE A. Principles And Practices Of YES NO YES NO Radiation Protection B. Radioactivity Measurement Standard- Ization Monitoring YES NO YES NO Techniques And Instruments C. Mathematics And Calculations Basic To The Use And YES NO YES NO Measurement Of Radioactivity D. Biological Effects Of Radiation YES NO YES NO III. EXPERIENCE (Use supplemental sheets as needed) A. RADIOACTIVE MATERIALS YES NO (Describe below) RADIONUCLIDE MAXIMUM AMOUNT LOCATION TYPE OF USE DURATION B. ACCELERATOR OR X-RAY EQUIPMENT YES NO (Describe below) DURATION **TYPE** MAXIMUM ENERGY LOCATION TYPE OF USE IV. REFERENCE DOCUMENTS I HAVE READ AND UNDERSTAND APPLICABLE PORTIONS OF THE FOLLOWING: KHB 1860.1 YES NO NRC REGULATIONS, 10 CFR 19 AND 20 YES NO N/A KMI 1860.1 (If applicable) YES NO N/A ESMCR 160-1 (If applicable) YES NO N/A FLORIDA REGULATIONS, CHAPTER 10D-56 YES NO N/A SIGNATURE OF APPLICANT DATE V. AUTHORIZATIONS HEALTH PHYSICS DATE KSC RADIATION PROTECTION OFFICER DATE ESMC RADIATION PROTECTION OFFICER DATE CHMN, KSC RADIATION PROTECTION COMMITTEE DATE (If applicable)

FIGURE A.9 RADIATION TRAINING AND EXPERIENCE SUMMARY (IONIZATION RADIATION) FORM

RADI		MATERIAL USE original and four copies;			
	(Frepare in				
FROM (NAME) (Please print)		OFFICE CODE		DATE	REF. NUMBER*
TO: KSC RADIATION PROTECTION OFFICER (RPO)		<u> </u>			
VIA					
HEALTH PHYSICS SECTION (OMEHS)					
	RADIOAC'	TIVITY REQUIREMENTS			
A. ELEMENT AND ISOTOPE			B. PHYSICAL FOR	М	
C. TOTAL QUANTITY REQUIRED (MC OR UNITS)			D. ESTIMATED	ACTIVITY PER	EXPERIMENT
,			(MC OR UNITS)		
E. WASTE CONCENTRATIONS & AMOUNTS	LIQUID	<u> </u>		SOL	
				D	
2. TITLE OR BRIEF DESCRIPTION OF PROPOSED PROJ	ECT				
		data.			
				<u> </u>	
2. PROPOSED PROCEDURE (INC.) LIDING SPECIAL DRE	CALITIONS				
3. PROPOSED PROCEDURE (INCLUDING SPECIAL PRE	CAUTIONS)				 :
			3A. LICENSE NO.		3B. NRC
			JA. LICENSE NO.		STATE OF
4. LOCATION OF USE	BUILDING		. 1	ROOM NUMBER	AREA ZONE
	NUMBER				NUMBER
5. USERS		6. PERIOD COVERED	BY REQUEST		
		FROM	то		
7. HEALTH PHYSICS EQUIPMENT REQUIREMENTS					
ORIGINATOR			SUPERVISOR'S SIG	NATURE	
					
APPROVALS					. <u> </u>
SIGNATURE (OMEHS HEALTH PHYSICS)					DATE
SIGNATURE (KSC RADIATION PROTECTION OFFICER))				DATE
SIGNATURE (CHAIRMAN RSC)					DATE

KSC Form 16-295NS (Rev. 5/77)

FIGURE A.10 RADIOACTIVE MATERIAL USE REQUEST

IONIZING RADIATION SOURCE DATA SHEET SPACE FLIGHT HARDWARE AND APPLICATIONS

Lyndon B. Johnson Space Center

IDENTIFICATION						
1. PAYLOAD DESIGNATION/EXPERIMENT		2. STS NO. AND/OR LAUNCH DAT	E			
3. SOURCE USING ORGANIZATION		4. ADDRESS				
5. CONTACT		6. TELEPHONE				
7. PAYLOAD SPONSOR/MANAGER		8. ADDRESS				
9. CONTACT		10. TELEPHONE				
PART A. RADIOISOTOPE SOURCES						
I. SOURCE DESCRIPTION						
1. ISOTOPE	1	L QUANTITY (MILLICURIE) determination date.)	3. NUMBER OF SOURCES			
4. CHEMICAL FORM		5. PHYSICAL STATE				
6. SOURCE SEALED		7. IDENTIFICATION NOS.	***************************************			
0 Yes 0 No		1				
8. MANUFACTURER		9. ADDRESS	9. ADDRESS			
II. SOURCE USE DATA						
1. PURPOSE: 0 EXTERNAL CALIBRATI 0 OTHER (Describe) 0 CREW INVOLVEMENTA		0 INFLIGHT CALIBRATION MENTS (Include nominal and contingent s	situations)			
III. SOURCE DIAGRAM		The state of the s	statovno./			
DETAILS ON SEALING, TECHNIQUES	AND DIME	NSIONS:				
JSC FORM 44 (Rev Oct 81)			*I jet individual course aventite			

FIGURE A.11 IONIZING RADIATION SOURCE DATA SHEET

IV. TEST DATA				
1. DATA SOURCE LEAK TESTED	2. RESULTS (MICROCURIE)			
	,			
3. THERMO-VACUUM	QUALIFIED TO:			
	DATE			
MM HG	DEGREE C.			
V. PRE-FLIGHT TRANSFERS				
1. LOCATIONS WHERE SOURCE IS TO BE USED OR STORED A	ND APPROXIMATE DATES			
A. LOCATIONS B. DATED FROM				
D. DATED PROM	то			
2. SOURCE CUSTODIAN/RADIATION SAFETY OFFICER	TELEPHONE			
, and the second	TELEPHONE			
VI. POST-FLIGHT DISPOSITION				
OUTLINE REQUIREMENTS:				
•				
PART B. IONIZING RADIATION PRODUCING EQUIPMENT				
I. EQUIPMENT CHARACTERISTICS				
1. TYPE OF RADIATION PRODUCED:				
THE TAXABLE STATE OF THE STATE				
2. MAXIMUM ENERGY LEVEL	2 OF DATING FUEDOW			
	3. OPERATING ENERGY LEVEL			
4. DURATION OF OPERATION	E NO OF HUMAN			
The state of the s	5. NO. OF UNITS			
HOURS TOTAL, ALL UNITS	6. PULSED UNIT DUTY CYCLE			
II. RADIATION CHARACTERISTICS				
RADIATION INTENSITY OF FLIGHT CONFIGURED UNIT				
T. NADIATION INTENSITY OF FLIGHT CONFIGURED UNIT	2. SECONDARY RADIATIONS PRODUCED			
	ENERGY LEVEL TYPE			
DADUID 65 METERS				
RAD/HR @METERS	KEV			
III. EQUIPMENT USE DATA				
1. CREW INVOLVEMENT/PROCEDURES:				
2. RADIATION PRODUCTION WARNING SYSTEM:	3. SAFETY INTERLOCK SYSTEM:			
O Von /Densite)				
0 Yes (Describe) 0 No	0 Yes (Describe) 0 No			
	-			
	NASA_ISI			

FIGURE A.11A IONIZING RADIATION SOURCE DATA SHEET (CONT'D)

TRAINING & EXPERIENCE SUMMARY NON-IONIZING RADIATION USERS

	NON-IONIZING (PLEASE TY)							
(NOTE - Co	OMPLETE UNSH				RM (ONLY)		
	1. GENERA	AL INFORMA	TION					
A. NAME	B. DATE OF BIR	TH.	C. OF	RGANIZA	TION	MAIL CO	DDE	D. REFERENCE NO.
E. SOC SEC NO. E. TY	PE OF USER						F. SYSTEM	/DEVICE TO BE USED
0 area	RADIATION OF	FICER	0 M	1AINTE	NAN	CE		
0 OPER	RATOR		0 o	THER				
II. TRA	AINING (USE SUPI	PLEMENTAL :	SHEET	S AS NE	EDEI	D)		
TYPE OF TRAINING	YES	NO		W	HERI	ETRAI	NED	DURATION
A. Biological Effects			1					
B. Radiation Protection								
C. Other								
III. EXPI	ERIENCE (USE SUI	PPLEMENTAL	SHE	ETS AS N	IEEDI	ED)		
TYPE OF EXPERIE	ENCE				LOG	CATION	Ĭ	DURATION
A.			1					
В.		•						
				-				
C.								
D.								
	IV. REFERI	ENCE DOCU	 MENT	S				
	I have read and	understand th	ie follo	owing:				
A. KMI 1860.1			0 Y	_	0	No		
В. КНВ 1860.2			0 x	l'es	0	No		
C. 29 CFR 1910.97			0 x	l'es	0	No		
D. ESMC Regulation 16()-1 (If Applicable)		0 x	l'es	0	No	0 N/A	
Signature o	f Applicant							Date
	V. AUT	HORIZATIO	NS					
HEALTH PHYSICS								DATE
KSC RADIATION PROTECTION OFFICER								DATE
ESMC RADIATION PROTECTION OFFICER (IF	F APPLICABLE)							DATE
CHMN. KSC RADIATION PROTECTION COMM	MITTEE							DATE

FIGURE A.12 TRAINING AND EXPERIENCE SUMMARY NON-IONIZING RADIATION USERS FORM

NOI	N-IONIZING RADIAT SOURCE QUESTI (PLEASE TYPE/PRII	IONNAIRE	N
ORIGINATOR	ORG/MAIL CODE	PHONE	DATE
SUPERVISOR	ORG/MAIL CODE	PHONE	DATE
(1	DEVICE/SYSTEM D USE SUPPLEMENTAL SH		
ТУРЕ	JOB OCT T DEMENTING BIT	ECTO NO MEDECEO	
0 radiofrequency/m	IICROWAVE		0 LASER/OPTICAL
MANUFACTURER AND YEAR		•	
MODEL AND SERIAL NO.			
FREQUENCY/WAVELENGTH			
MAX. POWER OUTPUT			
PULSE WIDTH			
REPETITION FREQ.		·- · · · · · · · · · · · · · · · · · ·	
USE LOCATION(s) SITE(s)			
INTENDED USE(s)			
ANTENNA DAT	A		ASSOCIATED OPTICS
TYPE AND QUANTITY		LENSES	
DIMENSIONS		FILTERS	
GAIN		OTHER	
RADIATION PROTECTION CONTROLS	EMPLOYED/IDENTIFI	ED ED	

KSC FORM 16-453 (REV. 4/81)			

FIGURE A.13 NON-IONIZING RADIATION PROTECTION SOURCE QUESTIONNAIRE

A5. SAFETY DATA PACKAGE (SDP)

A Flight Safety Data Package (SDP) and a Ground SDP is prepared for each payload. The Flight SDP is limited to payload design and flight operations and the Ground SDP focuses on ground hazards that might exist during pre-launch and post-landing periods. The SDP's are written to the same level of detail as a design review, but the emphasis is directed toward how the hardware complies with applicable safety requirements, as well as control of identified hazards, rather than operational performance requirements. The packages are the result of detailed analysis of the payload systems, GSE, system/component interfaces, procedures and possible hardware failure/human error combinations. This analysis is done to insure not only that nominal or generic safety requirements are met, but that any additional hazards are identified and adequately controlled. The preliminary SDP is prepared after the Payload Accommodations Conference. After final GSFC approval, the HH Mission Manager will submit the Phase O/I Flight SDP to the STS Payload safety review panel at JSC and the Ground SDP to the review panel at KSC for approval. Phase II and III SDPs will be prepared and submitted by GSFC with inputs from the payload organization. The following chart provides an example outline for the SDP.

EXAMPLE FLIGHT SAFETY DATA PACKAGE (SDP) OUTLINE

SECTION

- I. Table Of Contents
- II. Acronyms Abbreviations
- III. Figures And Diagrams
- 1.0 Introduction
- 1.1 Objectives
- 1.2 Applicable Documents
- 1.3 Concept
- 1.4 Operational Scenario
- 2.0 Payload Description
- 2.1 Overall Payload Description
- 2.1.1 Structural
- 2.1.2 Electrical
- 2.1.3 Cryogenics
- 2.1.4 Radiation
- 2.1.5 Pyrotechnics
- 2.1.6 Pressure System
- 2.1.7 Materials
- 2.1.8 Thermal
- 2.2 Hitchhiker Hardware Description
- 2.2.1 Mounting Plate
- 2.2.2 Adapter Beam
- 2.2.3 Canister
- 2.2.4 Hh Avionics
- 2.3 Flight Operations
- 3.0 Flight Safety Assessment And Verification
- 3.1 General
- 3.2 Integrated Payload/Hh Hazard Analysis
- 3.3 Payload Verification

Appendix A - Hazard Reports

A Similar Outline Should Be Followed For The Ground SDP And Include Ground Operations.

PAYLOAD SYSTEM SAFETY DATA SUBMITTAL SUMMARY

DATA SUBMITTAL SUMMARY					
Data Submittal	Submittal to GSFC	Updated Submittal to JSC			
Flight Safety Data Compliance Package					
Phase 0/I					
SCDP	L-18 Months	L-16 Months			
Presentation & Action Item Responses	L-17 Months	L-15 Months			
Phase II					
SCDP	L-12 Months	L-10 Months			
Presentation & Action Item Responses	L-11 Months	L-9 Months			
Phase III					
SCDP	L-8 Months	L-6 Months			
Presentation & Action Item Responses	L-7 Months	L-5 Months			
Ground Safety Data Compliance Package					
Phase 0/I					
SCDP	L-18 Months	L-16 Months			
(Operations Procedures List & MSDSs)					
Presentation & Action Item Responses	L-17 Months	L-15 Months			
Phase II					
SCDP	L-12 Months	L-10 Months			
(Preliminary Operations & Hazardous					
Procedures)					
Presentation & Action Item Responses	L-11 Months	L-9 Months			
Phase III					
SCDP	L-8 Months	L-8 Months			
Presentation & Action Item Responses	L-7 Months	L-5 Months			
Launch Site Safety					
Final Launch Site Safety documentation					
including: list of names of KSC I&T teams,	75 days prior to shipping to				
function and organization, KSC Operations	KSC				
Procedures, and Final Hazardous Operations					
Procedures					
Verification Tracking					
Ground VTL	L-4 Months	Semi-Weekly Updates			
Flight VTL	L-12 Months	Following Phase III Review			
Fraum A 14 Pour our Cuarre					

FIGURE A.14 PAYLOAD SYSTEM SAFETY DATA SUBMITTAL SUMMARY




FIGURE A.15 HH SAMPLE MISSION EXPERIMENT SAFETY SCHEDULE




FIGURE A.15 (CONTINUED)




FIGURE A.15 (CONTINUED)




FIGURE A.15 (CONTINUED)